



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-205+	EP-305+
Printing Methode	direct thermal and thermal transfer	
Control Panel	2 buttons, colour LCD panel with touch control	
Printing Resolution	203 dpi	300 dpi
Printing Speed (max.)	300 mm/s	250 mm/s
Printing Width (max.)	104 mm (4")	
Printing Length (min. - max.)	6,35 - 2539,7 mm (0.25" - 99.99")	6,35 - 1625,6 mm (0.25" - 64")
Media Width (min. - max.)	25,4 - 118 mm (1" - 4,6")	
Label Roll Diameter (max.)	200 mm (8")	
Core Diameter	25 - 75 mm (1" - 3")	
Media Types	Continuous form, gap labels, black mark sensing, cardboard ca. 200 - 254 g/m ² thermo- and transfer material	
Sensor Types	adjustable transmissive and reflectivesensor	
Ribbon Types	wax, wax/resin, resin	
Ribbon Length	up to 350 m (outside or inside wound)	
Interfaces	USB-A, USB-B, LAN	
Memory SDRAM	256 MB (24 MB for user)	
Memory Flash	256 MB (4 MB for user)	
Printerdriver	Windows, Linux	
Emulation	Datamax DMX, Zebra ZPL2, Eltron EPL2, Cross-Emulation automatic switsch	
Fonts	7 alphanum. Fonts, OCR A, B, ASD smooth Font up to 24 x expandable, rotatable 0° - 270° (depending on Emulation)	
Barcodes (1-dimensional)	all common 1-dimensionale barcodes	
Barcodes (2-dimensional)	Datamatrix, PDF-417, Maxicode	
Dimensions (B x L x H)	255 x 490 x 265 mm	
Weight	13,3 kg	
Options	cutter, dispencer, external unwinder, Premium-Ethernet-Interface, WLAN	
Item Number	30205500	30305500