



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-207+	EP-307+
Printing Methode	direct thermal and thermal transfer	
Printing Resolution	203 dpi	300 dpi
Printing Speed (max.)	200 mm/s (8")	150 mm/s (6")
Printing Width (max.)	104 mm (4")	
Printing Length (min. - max.)	6,4 - 4013 mm (0,25" -158")	
Media Width (min. - max.)	12,5 - 118 mm (0,5" - 4,6")	
Label Roll Diameter (max.)	200 mm (8")	
Core Diameter	25 - 75 mm (1" - 3")	
Media Type	continuous form, gap labels, black mark sensing, cardboard ca. 200-254 g/m ² thermo- and transfer material	
Sensor Types	adjustable transmissive and refelective sensor	
Ribbon	wax, wax/resin, resin	
Ribbon Length	up to 350 m (outside or inside wound)	
Interfaces	USB 2.0, 10/100 Ethernet	
Memory SDRAM	32 MB (4 MB for user)	
Memory Flash	16 MB (4 MB for user)	
Printerdriver	Windows, Linux	
Emulation	Datamax DMX, Zebra ZPL2, Eltron EPL2, Cross-Emulation automatic switch	
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes	
Barcodes (2-dimensional)	Datamatrix, PDF-417, Maxicode	
Dimensions (B x L x H)	250 x 458 x 261 mm	
Weight	11 kg	
Options	cutter, diespencer, external rewinder, Parallel IEEE1284, Serial RS232C, Premium Ethernet	
Item Number	30207100	30307100