



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-225	EP-235
Printing Methode	direct thermal and thermal transfer	
Control Panel	Color TFT LCD with navigation buttons, Calibration button	
Printing Resolution	203 dpi	300 dpi
Printing Speed (max.)	177 mm/s (7 IPS)	127 mm/s (5 IPS)
Printing Width (max.)	104 mm (4,09")	
Printig Length(min. - max.)	4 - 2540 mm (0,16" - 100")	4 - 1143 mm (0,19" - 45")
Media Width (min. - max.)	25,4 - 118 mm (0,8" - 4,65")	
Label Roll Diameter (max.)	203 mm (8") with 76,2 mm (3") core, 152,4 mm (6") with 38,1 mm (1,5") core	
Core Diameter	38 - 76 mm (1,5" - 3")	
Media Type	continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming	
Sensor Types	adjustable reflective sensor and transmissive sensor, left aligned	
Ribbon	Wax, Wax/Resin, Resin	
Ribbon Length	up to 450 m (1476")	
Interface	seriell RS232, USB 2.0 (B-Type), Ethernet, USB Host (A-Type)	
Memory SDRAM	16 MB SDRAM	
Memory Flash	8 MB (4 MB for user)	
Printerdriver	Windows, MAC, Linux	
Emulationen	EZPL, GEPL, GZPL, GDPL auto switch	
Fonts	Bitmap Fonts: 6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A & B, Bitmap Fonts in 90° steps rotatable, downloadable Fonts, TTF Fonts: TTF Fonts (Bold / Italic / Underline). 0°, 90°, 180°, 270° rotatable	
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes	
Barcodes (2-dimensional)	Aztec Code, Code 49, Codablock F, Datamatrix, Maxicode, Micro PDF-417, QR-Code, TLC 39, GS1 Composite	
Dimensions (B x L x H)	274 x 512 x 291 mm	
Weight	15,0 kg	
Options	Cutter module, Label Dispencer + internal rewinder module, external label rewinder, Centronics Interface, WLAN (IEEE 802.11 b/g/n combo module, Applikator Interface (DSUB female 15-pin)	
Item Number	30225000	30235000