



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-266
Printing Methode	direct thermal and thermal transfer
Printing Resolution	203 dpi
Printing Speed (max.)	150 mm/s (6 IPS)
Printing Width (max.)	168 mm (6")
Printing Length (min. - max.)	6,35 - 812,8 mm (0,25" - 32")
Media Width (min. - max.)	50 - 178 mm (2" - 7")
Label Roll Diameter (max.)	125 mm (5")
Core Diameter	26 mm (1" - 3")
Media Type	Continuous form, gap labels, black mark sensing, cardboard ca. 200-254 g/m ² thermo- and transfer material
Sensor Types	adjustable reflective sensor and transmissive sensor
Ribbon	Wax, Wax/Resin, Resin
Ribbon Length	up to 360 m (outside- or inside winded)
Interface	RS232, USB 2.0
Memory SDRAM	32 MB (1 MB for user)
Memory Flash	8 MB (1 MB for user)
Printerdriver	Windows, MacOS, Linux
Emulation	Datamax DMX, Zebra ZPL2, Eltron EPL2, Cross-Emulation automatic switch
Fonts	7 alphanum. Fonts, OCR A, B, ASD smooth Font bis zu 24-fach vergrößerbar, drehbar 0° - 270° (abhängig von der Emulation)
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes
Barcodes (2-dimensional)	Datamatrix, UPS Maxicode, PDF-417, QR-Code
Dimensions (B x L x H)	303 x 290 x 273 mm
Weight	7,9 kg
Options	Cutter, dispencer, external unwinder, Ethernet-Interface (10/100 BaseT), WLAN-Interface, Centronics-Interface
Artikelnummer	30266000