



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-820	EP-830	EP-860
Printing Methode	direct thermal and thermal transfer		
Control Panel	Color LCD display with navigation buttons, calibration button on backside		
Printing Resolution	203 dpi	300 dpi	600 dpi
Printing Speed (max.)	254 mm/s (10 IPS)	177 mm/s (7 IPS)	102 mm/s (4 IPS)
Printing Width (max.)	104 mm (4,09")		
Printing Legth (min. - max.)	4 - 4572 mm (0,12" - 279,53")	4 - 2159 mm (0,12" - 125,98")	4 - 660 mm (0,12" - 31,5")
Media Width (min. - max.)	25,4 - 104 mm (up to 4,09")		
Label Roll Diameter (max.)	203,2 mm (80")		
Core Diameter	38,1 - 76,2 mm (1,5" - 3")		
Media Type	continuous form, gap labels, black mark sensing, and punched hole;label lengthset by auto sensing or programming		
Sensor Types	adjustable reflective sensor and transmissive sensor, left aligned		
Ribbon	Wax, Wax/Resin, Resin		
Ribbon Length	bis 450 m (1476")		
Interface	USB 2.0, RS232, Ethernet, 3x USB Host (Type A)		
Memory SDRAM	32 MB		
Memory Flash	128 MB (60 MB for user)		
Printerdriver	Windows, MAC, Linux		
Emulation	EZPL, GEPL, GZPL, GDPL auto switch		
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes		
Barcodes (2-dimensional)	Aztec code, Code 49, Codablock F, Micro QR, Maxi Code, Datamatrix, Micro PDF-417, TLC 39, QR Code, PDF-417, GS1 Compos.		
Dimensions (B x L x H)	305 x 465 x 263 mm		
Weigth	13,6 kg		
Options	Dispencer + intern rewinder, Cutter, Parallel Interface (Centronic female 36-pin), WLAN Print Server, Applikator Interface(DSUB female 15-pin), ext. rewinder, Bluetooth Modul		
Item Number	30820000	30830000	30860000