



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-P4-250	EP-P4-350	EP-P4-650
Printing Methode	Thermodirekt und Thermotransfer		
Printing Resolution	203 dpi	300 dpi	600 dpi
Printing Speed (max.)	152,4 mm/s (6 ips)	101,6 mm/s (4 ips)	Max. 4ips (101.6mm/s); Max. 3ips (76.2mm/s) for peel off mode
Printing Width (max.)	108 mm (4,25")	105,7 mm (4,16")	105,7mm (4,16")
Printing Length (min. - max.)	bis 2540 mm (100")	bis 1270 mm (50")	bis 762 mm (30")
Media Width (min. - max.)	22,4 - 118 mm (4,65")		
Rollendurchmesser (max.)	127 mm (5")		
Rollenkerndurchmesser	25,4 - 38 mm (1" - 1,5")		
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper		
Sensor Types	Reflective sensor x 1 (movable) & Transmissive sensor x 1 (fixed, 6.27mm offset)		
Ribbon	Wax, Wax/Resin, Resin		
Ribbon Length	300 m		
Interfaces	USB 2.0, RS232, Ethernet, USB Host		
Memory SDRAM	32 MB SDRAM		
Memory Flash	16 MB		
Printerdrivers	Windows, Linux, macOS		
Emulation	PPLA, PPLB, PPLZ, Auto		
Fonts	Internal character sets standard, 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation.		
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes		
Barcodes (2-dimensional)	QR-Code, PDF-417 (inkl. Micro PDF), Datamatrix, Maxicode		
Dimensions (B x L x H)	220,6 x 278,5 x 187,5 mm		
Weight	2,4 kg		
Options	Cutter, Dispencer, external Rewinder, external Unwinder, Bluetooth-Modul, WLAN		
item number	37425000	37435000	37465000