



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-iX4-250	EP-iX4-350
Printing Methode	direct therma and thermal transfer	
Printing Solution	200 dpi	300 dpi
Printing Speed (max.)	203,2 mm/s (8 ips)	152,4 mm/s (6 ips)
Printing Width (max.)	105 mm (4,13")	104 mm (4,08")
Printing Length (min. - max.)	5 - 2540 mm (max 100")	5 - 1270 mm (max 50")
Media Width (min. - max.)	25,4 - 114 mm (4,13")	
Label Roll Diameter (max.)	210 mm (8,26") with 76 mm (3") core	
Core Diameter	38,1 - 76,2 mm (1,5" - 3")	
Media Type	roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper	
Sensor Types	moveable refelctive & transmissive sensor	
Ribbon	Wax, Wax/Resin, Resin	
Ribbon Length	up to 450 m	
Interface	USB, RS232, Ethernet, 2x USB host	
Memory SDRAM	128 MB	
Memory Flash	128 MB	
Printerdriver	Windows, Linux, Mac OS	
Emulation	PPLA, PPLB, PPLZ, Auto	
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes	
Barcodes (2-dimensional)	QR Code, PDF-417, Micro PDF-417, Datamatrix, GS1 Datamatrix, Maxi Code	
Dimensions (B x L x H)	257 x 432 x 263 mm	
Weight	13 kg	
Options	Cutter, Dispencer, WLAN	
Item Number	34251000	34351000