



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-iX6-250 Pro	EP-iX6-350 Pro
Printing Methode	direct thermal and thermal transfer	
Printing Resolution	203 dpi	300 dpi
Printing Speed (max.)	152,4 mm/s (6 ips)	
Printing Width (max.)	168 mm (6,6")	
Printing Length (min. - max.)	5 - 2540 mm (100")	5 - 1270 mm (50")
Media Width (min. - max.)	50,8 - 173 mm (2" - 6,8")	
Label Roll Diameter (max.)	210 mm, bei 76er Kern (8,26" on a 3" core)	
Core Diameter	38,1 - 76,2 mm (1,5" - 3")	
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper	
Sensor Types	adjustable reflective sensor and transmissive sensor	
Ribbon	Wax, Wax/Resin, Resin	
Ribbon Length	up to 450 m (1476")	
Interface	USB, RS232, Ethernet, 2x USB host	
Memory SDRAM	128 MB	
Memory Flash	128MB (USB Memory up to 32GB)	
Printerdriver	Windows, Linux, MacOS	
Emulation	PPLA, PPLB, PPLZ, Auto	
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes	
Barcodes (2-dimensional)	QR Code, PDF-417, Micro PDF-417, Datamatrix, GS1 Datamatrix, Maxi Code	
Dimensions (B x L x H)	257 x 432 x 263 mm	
Weigth	13 kg	
Options	Cutter, Dispencer, internal Rewinder, WLAN	
Item Number	36251000	36351000