



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.de>

Specs:	EP-105+
Print Method	Thermal Transfer / Direct Thermal
Resolution	203 dpi
Print Speed (max.)	178 mm/s (up to 7 ips)
Print Width (max.)	54 mm (2,12")
Print Length (min. - max.)	4 - 1727 mm (0,16" - 68")
Media Width (min. - max.)	15 - 60 mm (0,6" - 2,36")
Label Roll Diameter (max.)	127 mm (5")
Core Diameter	ab 26 mm (1" - 1,5")
Media Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
Sensor Type	Adjustable reflective sensor (full range). Fixed transmissive sensor, central aligned
Ribbon	Wax, wax/resin, resin
Ribbon Length	110 m (360') außen
Interfaces	USB 2.0, RS232, Ethernet, USB host
Memory SDRAM	16 MB SDRAM
Memory Flash	8 MB (4 MB for user storage)
Printerdriver	Windows 7, Windows 8 & 8.1, Windows 10, Windows 11, Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019, 2022, MAC, Linux
Fonts	9 alphanumeric fonts and OCR A & B, Bitmap fonts 90°, 180° and 270° rotatable and 8-times expandable, other fonts can be downloaded
Barcodes (1-dimensional)	all common 1-dimensional barcodes
Barcodes (2-dimensional)	UPS Maxicode, PDF-417, QR-Code, Micro PDF-417, Code 49, Aztec Code, Codablock F, Datamatrix, Micro QR, TLC 39, GS1 Composite
Dimensions (B x L x H)	136 x 245 x 175 mm (5,35" x 9,65" x 6,91")
Weight	1,65 kg
Options	Cutter module, Label dispenser, WiFi, BT, external label unwinder, external label rewinder
item number	30105100