



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.de>

Specs:	EP-105
Printe Methode	Direct thermal
Resolution	203 dpi
Print Speed (max.)	177 mm/s (up to 7 ips)
Print Width (max.)	54 mm (2,12")
Print Length (min. - max.)	4 - 1727 mm (0,16" - 68")
Media Width (min. - max.)	15 - 60 mm (0,6" - 2,36")
Label Roll Diameter (max.)	127 mm (5")
Core Diameter	ab 26 mm (1")
Media Types	Continuous form, gap labels, black mark sensing, and punched hole; label lengthset by auto sensing or programming
Sensor Types	Adjustable reflective sensor (full range). Fixed transmissive sensor, central aligned
Ribbon	---
Ribbon Length	---
Interfaces	USB, RS232, Ethernet
Memory SDRAM	16 MB SDRAM
Memory Flash	8 MB (4 MB for user)
Printerdriver	for Windows, MAC, Linux
Fonts	9 alphanumeric Fonts and OCR A & B
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes
Barcodes (2-dimensional)	UPS Maxicode, PDF-417, QR-Code, Micro PDF-417, Code 49, Aztec Code, Codablock F, Datamatrix, Micro QR, TLC 39, GS1 Composite
Dimensions (B x L x H)	100 x 218 x 172 mm (8,15" x 6,73" x 4,41")
Weight	1,2 kg
Options	Cutter module, label dispencer, external rewinder, external label unwinder, keyboard for stand-alone-mode
item number	30105000