



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Tel: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	Rabbit 214+ E
Printing Methode	Direct Thermal & Thermal Transfer
Printing Resolution	203 dpi
Printing Speed (max.)	152 mm/s (6ips)
Printing Width (max.)	108 mm (4,25")
Printing Length (min. - max.)	max. 2540 mm (100")
Media Width (min. - max.)	25,4 - 110 mm (0,8" - 4,3")
Media Roll Diameter (max.)	127 mm (5")
Core Diameter	12,7 - 38,1 mm (0,5" - 1,5")
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper
Emulation	PPLA, PPLB, PPLZ
Sensor Types	Fixed reflexive sensor
Ribbon	Wax, Wax/Resin, Resin
Ribbon Length	85 m (1/2") outside
Interfaces	Ethernet, USB, USB host, RS232
Memory SDRAM	32 MB SDRAM
Memory Flash	16 MB
Printerdrivers	Windows, LINUX Driver, macOS Driver
Fonts	5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes
Barcodes (2-dimensional)	UPS Maxicode, QR-Code, PDF-417 (inclu. Micro PDF), Datamatrix (ECC200), GS1 Datamatrix
Dimensions (B x L x H)	182,5 x 282 x 173 mm
Weight	1,54 kg
Options	Cutter, external Rewinder, Large roll unwinder, Keyboard für Stand-alone-Betrieb
item number	30214200