



ETISYS Etikettierlösungen GmbH
 Heidenberg 7
 D-87672 Roßhaupten
 Fon: +49 (0) 83 67 / 9 13 99 - 0
 Fax: +49 (0) 83 67 / 9 13 99 - 90
 Mail: info@etisys.de
 Internet: <https://www.etisys.eu>

Specs:	EP-120+ PRO	EP-130+ PRO
Print Method	Thermal Transfer / Direct thermal	
Control Panel	Color TFT LCD display with navigation buttons, calibration button on the back	
Resolution	203 dpi	300 dpi
Print Speed (max.)	178 mm/s (up to 7 ips)	127 mm/s (up to 5 ips)
Print Width	108 mm (4,25")	105,7 mm (4,16")
Print Length (min. - max.)	3 - 10160 mm (0,12" - 400")	3 - 8890 mm (0,12" - 350")
Media Width (min. - max.)	25,4 - 118 mm (4,25")	25,4 - 105,7mm (4,16")
Label Roll Diameter(max.)	127 mm (5")	
Core Diameter	25,4 - 38,1 mm (1" - 1,5")	
Media Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming	
Sensor Types	Adjustable reflective sensor (full range). Fixed transmissive sensor, central aligned	
Ribbon	Wax, wax/resin, resin	
Ribbon Legth	300 m	
Interfaces	USB 2.0, RS232, Ethernet, IEEE 802.1X Protokoll Support, 2 USB Host	
Memory SDRAM	512 MB SDRAM	
Memory Flash	16 GB	
Printerdriver	for Windows, MAC, Linux	
Printer Language	EZPL, GEPL, GZPL, GDPL automatic detect	
Fonts	9 alphanumeric fonts and OCRA & B, Bitmap fonts 90°, 180°and270° rotatable and 8-times expandable, other fonts can be downloaded	
Barcodes (1-dimensional)	all common 1-dimensionale Barcodes	
Barcodes (2-dimensional)	Datamatrix, Maxicode, PDF-417, Micro QR-Code, QR-Code, Aztec Code, Code 49, Codablock F, TLC 39, GS1 Composite, DotCode, Macro PDF 417	
Dimensions (B x L x H)	210 x 280 x 186 mm (11,0" x 8,46" x 7,36")	
Weight	2,6 kg	
Options	Cutter module, label dispenser, external rewinder, external label unwinder, Wireless connectivity: can be paired with a USB Wi-Fi or Bluetooth dongle to enable a wireless connection.	
item number	30120600	30130600