



Units 1-3 Shannon Industrial Estate  
Lodge Road  
Sandbach  
Cheshire  
CW11 3HP

e. [info@euroacc.co.uk](mailto:info@euroacc.co.uk)  
w. [www.euroacc.co.uk](http://www.euroacc.co.uk)

## Data Sheet

## Tying Wire

Black Soft Annealed Tying Wire is the most popular Tying Wire and is annealed to the highest standards.

| Product Code | Gauge | Coil Weight (kg) | Pallet Size (no) |
|--------------|-------|------------------|------------------|
| TW16         | 16    | 10               | 90               |
| TW17         | 17    | 9                | 100              |
| TW172        | 17    | 2                | 300              |



| Diameter             | Colour | Finish         | Tensile Test | Coil Packaging                |
|----------------------|--------|----------------|--------------|-------------------------------|
| 17G, 1.42mm +/- 0.02 | Black  | Slightly Oiled | Passed       | Inner Plastic / Outer Hessian |
| 16G, 1.57mm +/- 0.02 | Black  | Slightly Oiled | Passed       | Inner Plastic / Outer Hessian |

|                     | Allowed | Found | Notes:   |
|---------------------|---------|-------|--|
| Critical defectives | 0.0%    | 0     | <b>Critical defective:</b> A defect that judgment and experience indicate is likely to result in hazardous or unsafe conditions; product or assembly failure or regulations are not respected. |
| Major defectives    | 1.0%    | 0     | <b>Major defective:</b> A defect that judgment and experience indicate is likely to affect product performance or reduce the usability of the product for its intended purpose.                |
| Minor defectives    | 4.0%    | 0     | <b>Minor defectives:</b> A departure from established standards that is not likely to reduce the usability of the item or assembly for its intended purpose.                                   |