

VSS080N

VISIONCON.
Connector Systems & Solutions





ORDER CODE

VSS080N	-	XXP	-	1Y	-	00A
---------	---	-----	---	----	---	-----

Serie	no. of poles	pitch / color	special
	02 ~12P	1 = single pitch 2 = double pitch	A = customized

Y:	
1 = green	6 = red
2 = blue	7 = transparent
3 = black	8 = white
4 = grey	9 = yellow
5 = orange	Y = mixed (on request)



TECHNICAL DATA

Test Standrad	IEC 60998-2-1 / UL 1059		
Pitch [mm]	8		
No. of Poles	02 ~12 P		
IEC 60998-2-1			
Rated Insulation Voltage [V]	750		
Rated Current [A]	24		
Rated Connection Capacity (Solid / standed) [mm ²]	0.5 ~2.5		
Surge Voltage Category Pollution Degree/ Material Group	III / 2 / I		
Frequente Voltage [V]	AC 3000V 1Minute		
Rated Surge Voltage [V]	6000		
Rated Torque	0.4		
UL 1059			
Use Group	B	C	D
Rated Insulation Voltage [V]	600	./.	600
Rated Current [A]	15	./.	5
Rated Connection Capacity (Solid / standed) [AWG]	20 ~14		
Rated Tourque [N.m]	3.54		
OTHER DATA			
Ambient Temperature [°C]	-40°C ~ +105°C		
Stripping Length [mm]	6 ~7		
Plastic Material Imflammability Class	PA66 UL94 V-2		
Screw Specification Material/ Plating	Steel / Zn plated		
Conductor Material / Plating	Copper Alloy Ni plated		