## VSS100HWP

## VISIONCON.

Connector Systems & Solutions


(on request)






## ORDER CODE

VSS100HWP XXP 1Y 00A Serie no. of poles special pitch /color 02 ~12P 1 = single pitch A = customized2 = double pitch 6 = red1 = green2 = blue 7 = transparent 3 = black 8 = white 4 = grey 9 = yellow 5 = orange Y = mixed





## TECHNICAL DATA

Test Standrad	IEC 6	IEC 60998-2-1 / UL 1059		
Pitch [mm]		10		
No. of Pols		02 ~12 P		
IEC 60998-2-1	•			
Rated Insulation Voltage [V]		1000		
Rated Current [A]		24		
Rated Connection Capacity (Solid / standed) [mm <sup>2</sup> ]		2.5		
Surge Voltage Category Pollution Degree/ Material Group		III/2/I		
Frequente Voltage [V]	AC	AC 3000V 1Minute		
Rated Surge Voltage [V]		6000		
Rated Torque		0.5		
UL 1059				
Use Group	В	С	D	
Rated Insulation Voltage [V]	600	./.	600	
Rated Current [A]	20	./.	5	
Rated Connection Capacity (Solid / standed) [AWG]		18 ~12		
Rated Tourque [N.m]		4.43		
OTHER DATA				
Ambient Temperature [°C]	-	-40°c ~ +105°C		
Stripping Length [mm]		6 ~7		
Plastic Material Imflammability Class		PA66 UL94 V-2		
Screw Specification Material/ Plating	S	Steel / Zn plated		
Conductor Material / Plating / Wire Protection	Copper Alloy	Copper Alloy Ni plated / Stainless Steel		