

ZELLSTOFFPUFFER MIT GEWINDEBOLZEN



Material: Zelliges Polyurethan-Elastomer
Raumgewicht von 0,5 bis 0,55 g/cm³

Nenngröße size	Abmessung dimensions (mm)			Arbeitsaufnahme energy capacity kJ1	Federweg compression mm1	Endkraft endforce kn1	Stückgewicht unit weight kg		
	d1	h	d2 l						
80	40	M12	35	0,8	30		0,21		
	80			1,5	60	50	0,31		
	120			2,3	90		0,42		
100	50			1,5	38		0,31		
	100			3	75	80	0,52		
	150			4,4	113		0,73		
125	63			2,9	47		0,51		
	125			5,7	94	124	0,92		
	190			8,6	143		1,32		
160	80			6	60		0,95		
	160			12	120	200	1,80		
	240			18	180		2,66		
200	100	12	75		1,76				
	200	24	150	310	3,43				
	300	35	225		5,10				
250	125	M24	80	23	94		5,40		
	250			46	188	490	8,50		
	375			69	280		11,50		
315	158			47	120		8,50		
	315			93	236	780	14,65		
	475			140	356		20,80		
400	200			M30	80	94	150		16,50
	400					188	300	1250	29,10
	600					282	450		41,60

