



## **GBLC Primer**

### **DESCRIPTION**

GBLC primer is transparent acrylic co-polymer dispersion. It is a penetrating primer designed for application to Gypsum and Portland cement screed surfaces.

### **FEATURES**

- READY TO USE
- WATER BASED NON-FLAMMABLE
- LABORATORY CONTROLLED MANUFACTURE
- REDUCES SURFACE DUSTING
- AVAILABLE FROM STOCK.
- CONVENIENT 25 litre or 5 litre plastic containers.

### **COVERAGE**

4-7 m<sup>2</sup> per litre per coat. (depending on surface porosity)

### **AVAILABILITY**

The product is normally available from stock.

### **STORAGE**

Store in the original container in a cool area at a temperature in the range 5<sup>0</sup>c - 25<sup>0</sup>c.

PROTECT FROM FROST.

### **APPLICATION**

GBLC primer should be applied to the screed following the removal of laitance by sanding and vacuuming.

The surface should be clean, dry, and free from oil, grease, dust, laitance and any other deleterious materials. It should not be applied below 5<sup>0</sup>c or above 25<sup>0</sup>c.

Apply using short haired roller, squeegee, soft brush or by spray.

Avoid pooling of the primer during application.

The required topping can be applied in 0.5 - 1 hour depending on substrate porosity and/or ambient temperature.

Highly porous surfaces like sand/cement screeds may require a second coat 4 – 6 hours after the first coat.

---

**Unit 237, Oldfield Road, Walton Summit Ind Park, Bamber Bridge, Preston, Lancashire, PR5 8BG, England**

**Tel: 01772 335435 Fax: 01772 335434**

**Email: [sales@creative-impressions.com](mailto:sales@creative-impressions.com) Website: [www.creative-impressions.com](http://www.creative-impressions.com)**



Reg. Office: 237 Oldfield Road, Bamber Bridge, PR5 8BG.

